

Wechselobjektive für Hitachi CP-WX11000, CP-SX12000 und CP-X10000

Ultra short USL-801*	Short 1 SL-802	Short 2 SL-803	Standard SD-804	Long LL-805	Ultra long UL-806
					

Lichtstärke F	2,35 - 2,50	2,53 - 2,90	2,06 - 2,68	1,60 - 2,06	2,3 - 3,4	2,31 - 3,50
Brennweite f (mm)	13,8 - 16,5	34,0 - 40,8	40,2 - 58,6	59,9 - 77,8	77,4 - 139,3	136,0 - 247,0
Zoomverhältnis	1:1,2	1:1,2	1:1,5	1:1,3	1:1,8	1:1,8
Bilddiagonale (m)	1,02 - 17,78					

Throw-Ratio:

CP-X10000, CP-SX12000	0,52 - 0,62 : 1	1,29 - 1,54 : 1	1,52 - 2,22 : 1	2,27 - 2,95 : 1	2,93 - 5,27 : 1	5,15 - 9,35 : 1
CP-WX11000	0,53 - 0,63 : 1	1,29 - 1,55 : 1	1,53 - 2,23 : 1	2,28 - 2,96 : 1	2,95 - 5,3 : 1	5,18 - 9,4 : 1

Lens-Shift, vertikal

CP-X10000, CP-SX12000	1:1			3,7 : -1 bis -1 : 3,7		
CP-WX11000	1:1			2,3 : -1 bis -1 : 2,3		

Lens-Shift, horizontal

CP-X10000, CP-SX12000	1:1			13,0 : -1 bis -1 : 13,0		
CP-WX11000	1:1			10,5 : -1 bis -1 : 10,5		

Projektionsabstand:

Bildgiagonale 1,02 m (40")	0,4 - 0,5	0,9 - 1,2	1,1 - 1,7	1,7 - 2,3	2,2 - 4,2	3,9 - 7,4
Bilddiagonale 2,54 m (100")	1,0 - 1,2	2,5 - 3,0	3,0 - 4,4	4,4 - 5,8	5,7 - 10,7	10,2 - 18,8
Bilddiagonale 17,78 m (700")	7,4 - 8,7	18,0 - 21,7	21,3 - 31,2	32,0 - 41,6	41,3 - 75,6	72,8 - 132,8

Abmessungen:

Länge (mm)	241	246	276	251	258	286
Durchmesser (mm)	176	176	176	134	134	134
Gewicht (kg)	4,3	4,0	3,8	3,2	3,9	3,7

Medium Art.-Nr.	1905-801	1905-802	1905-803	1905-804	1905-805	1905-806
-----------------	----------	----------	----------	----------	----------	----------

*USL-801 eignet sich nur für Rückprojektionsanwendungen