



VIVITEK INTRODUCES NEW EXTREME SHORT-THROW PROJECTOR

The New D7 Short-Throw Series from Vivitek Delivers Picture Performance, Brightness and Crossover Possibilities

Vivitek Corporation, a leading manufacturer of environmentally innovative visual presentation products, introduces the D795WT Extreme Short-Throw digital projector for the education market. This D7 series consists of short-throw projectors that are ideal for small environments with big picture needs.

The D795WT is a native WXGA digital projector that can create a 95-inch image (diagonal) from about 1.3-feet away. Featuring DLP® and BrilliantColor™ technologies from Texas Instruments, the D795WT is 3D-ready and boasts 3000 lumens of brightness, a 2500:1 contrast ratio and up 6,000 hours of standard lamp-life.

“Vivitek wanted to bring an extreme short-throw projector to enhance our product line to customers,” said Christopher Yang, senior product manager at Vivitek. “With the technology resources at Vivitek, we developed the D795WT projector to fill the needs of the education market. From lamp life and brightness to connectivity options and 3D-Ready capability, the D795WT is an ideal projector for the classroom.”

Key Features/Specifications:

1. Native WXGA (1280x800) resolution
2. 3000 Lumens and 2500:1 Contrast Ratio
3. DLP® and BrilliantColor™ technologies from Texas Instruments
4. 6000 Hours of lamp life (standard mode); 4000 Hours of lamp life (boost mode)
5. Connectivity options include: HDMI v1.3, VGA-in (x2), Composite video, S-video
6. Top-loading, sliding cover for quick and easy lamp replacement
7. 9 kg; noise level of 27dB

Availability/Warranty

The Vivitek D795WT will be available in August 2010 through authorized Vivitek dealers and distributors. MSRP is TBD.

About Vivitek Corporation

Vivitek manufactures an extensive line of visual display and presentation products. The company's line of digital projection and display products incorporates the latest innovations and technologies to deliver superior products for its partners, customers and channels. Vivitek products are sold through authorized dealers, distributors, retailers and system integrators. For more information, visit www.vivitekcorp.com.

D795WT



Specifications

Brightness	3000 Lumens
Native Resolution	WXGA (1280 x 800)
Max. Resolution	UXGA (1600 x 1200)
Contrast Ratio	2500:1 (Full On/Off)
Lamp Life and Type	≈4000/6000 hr (Standard/Eco Mode), 200W
Display Type	Single DMD DLP® Technology
Throw Ratio	0.19:1
Screen Size (Diagonal)	86,75 – 95" (0.9 to 6.6 m)
Projection Distanz	14,96" (0,38 m)
Projection Linse	F= 2.4. Manual Focus
Aspect Ratio	16:10 native, 16:9 & 4:3 compatible
Keystone Correction	±15° vertical
Colours	16,7 Million
Horizontal Frequency	15, 31 - 91.4 KHz
Vertical Frequency	43 - 87 Hz
Speaker	10 Watt Mono
Remote Control	Card-Type IR Remote
Projection method	Table or ceiling mounted
Uniformity	85%
Computer signals	UXGA, SXGA, XGA, SVGA, VGA Resized; VESA Standards; PC and Macintosh Compatible
Video signals	SDTV (480i, 576i), EDTV (480p, 576p), HDTV (720p, 1080i/p), NTSC (M, 3.58/4.43 MHz), PAL (B, D, G, H, I, M, N), SECAM (B, D, G, K, K1, L)
Connections	HDMI 1.3, VGA-In 2x, S-Video, Composite Video, RCA Audio-In, Mini-Jack Audio-In
Security	Kensington® Lock Port
Weight	9 Kg
Dimensions	354 x 219 x 410.5 mm
Noise Level	27dB/29dB (Standard/Eco Mode)
Power	Supply: AC 100-240V, 50/60Hz Power: 240W (Eco Mode), 290W (Standard Mode), <1W (Standby Mode)
Operating Temperature	5 to 40°C
Warranty	3 Years, 1 Year or 1000 hr Lamp
Standard Accessories	Power Cable, VGA Cable, Remote Control, Batteries for Remote, User Manual (CD)



D795WT



Spezifikation

Helligkeit	3000 Lumen
Native Auflösung	WXGA (1280 x 800)
Max. Auflösung	UXGA (1600 x 1200)
Kontrast Ratio	2500:1 (Full On/Off)
Lamp Life und Type	≈4000/6000 Std (Standard/Eco Mode), 200W
Display Typ	Single DMD DLP® Technology
Throw Ratio	0.19:1
Bildgröße (Diagonal)	86,75 – 95" (0.9 to 6.6 m)
Projektionsdistanz	14,96" (0,38 m)
Projektionslinse	F= 2.4. Manueller Fokus
Darstellung	16:10 nativ, 16:9 & 4:3 kompatibel
Keystone Korrektur	±15° Vertikal
Farben	16,7 Million
Horizontale Frequenz	15, 31 - 91.4 KHz
Vertikal Frequenz	43 - 87 Hz
Lautsprecher	10 Watt Mono
Remote Control	Card-Type IR Remote
Projektionen	Tisch oder Deckenmontage
Uniformity	85%
Computer Signale	UXGA, SXGA, XGA, SVGA, VGA Resized; VESA Standards; PC and Macintosh Compatible
Video Signale	SDTV (480i, 576i), EDTV (480p, 576p), HDTV (720p, 1080i/p), NTSC (M, 3.58/4.43 MHz), PAL (B, D, G, H, I, M, N), SECAM (B, D, G, K, K1, L)
Anschlüsse	HDMI 1.3, VGA-In 2x, S-Video, Composite Video, RCA Audio-In, Mini-Jack Audio-In
Security	Kensington® Lock Port
Gewicht	9 Kg
Maße	354 x 219 x 410.5 mm
Noise Level	27dB/29dB (Standard/Eco Mode)
Power	Supply: AC 100-240V, 50/60Hz Verbrauch: 240W (Eco Mode), 290W (Standard Mode), <1W (Standby Mode)
Operating Temperatur	5 to 40°C
Garantie	3 Jahre, 1 Jahr oder 1000 Std Lampe
Standard Zubehör	Stromkabel, VGA Kabel, Fernbedienung, Batterien für FB, Gebrauchsanleitung (CD)